

Adhesive Reference

	Product	RH Limit ASTM 2170	Vapor Emission ASTM F1899	pH Limit	Weight (lbs) per Unit	Trowel Size and Usage Notes	Unit Size	Coverage per Unit	Recommended				TOLI®			C.I. TAKIRON			
									Wet or Flood Washed	Extreme Heat or Cold	Heavy Static Load	Custom Designs	Mature® AdVantage	Lightwood®/Kareina Asento®	Homogeneous Vinyl Tile	Nattice® & Pathways (Interior)*	Nattice & Pathways (Exterior)	Tread & Risers (Interior)	Tread & Risers (Exterior)
Adhesives	CBC® 5001 Acrylic	85%	6 lbs / 24 hours / 1,000 SF	10 pH	40.0	1/16 x 1/16 x 1/16 V-notch	4 Gallon	670-750 SF		◆		◆				P		P	
						1/16 x 1/16 x 1/16 V-notch	4 Gallon	720-800 SF		◆								N	
						1/32 x 1/16 x 1/32 U-notch	4 Gallon	880-1,040 SF		◆		◆	P	P	P				
						1/32 x 1/16 x 1/32 U-notch	4 Gallon	1,200-1,400 SF					N	N	N	N			
	CBC 951 Epoxy	90%	8 lbs / 24 hours / 1,000 SF		29.0	1/32 x 1/16 x 1/32 U-notch	1 Gallon	175-225 SF	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆
Tread Accessories	Opti-Tape 9.5" Width				7.3		1 roll/ctn	165 LF per roll										◆	
	CBC 800 Nose Caulk				1.7	Double Caulking Gun	13.5 oz. Tube	40 LF per tube		◆								◆	◆

P = Porous surface
 N = Non-porous surface
 ◆ = Porus & non-porous surface
 * = Interior wet areas follow exterior instructions