

TOLI Mature®AdVantage

Commercial Sheet with ClearGuard[™] Anti-Viral Wear Layer



TOLI Mature®AdVantage

Commercial Sheet with ClearGuard[™] Anti-Viral Wear Layer

Mature AdVantage is the industry's leading anti-viral AND anti-bacterial commercial sheet flooring making it the perfect solution for healthcare, assisted living, education and any other application requiring extra protection without sacrificing visual beauty.

Mature AdVantage print film is produced to exacting Japanese standards to deliver unmatched detail and realism. Our low-profile embossing and our unique ClearGuard™ wear layer combine to deliver a hygienic and attractive flooring solution that stands up to high-traffic environments for decades without the use of waxes or polishes.

When you step into a space, it's the experience that matters. When you're choosing the flooring to complete that space, experience matters even more. Celebrating over 100 years, TOLI has been the premier manufacturer of the world's most innovative floor coverings.

Trust the experience[™]. Trust TOLI.




GET SAMPLES FAST 919-230-8700 www.cbcflooring.com

Questions? Give us a call, we're ready to help you create your next great space.


How It Works

- 1. Flooring surface is exposed to viruses (via coughing, sneezing, shoe soles, etc.)
- 2. Mature AdVantage's permanent anti-viral properties are integrated into the upper-most portion of its ClearGuard wear layer and chemically bond with the viruses.
- 3. By degenerating or degrading the structure of the virus (including its membranes and shells), the viruses are destroyed.
- 4. Harmless fragments are eliminated through routine maintenance.



The Construction

- Layer 1 Clear UV coating. Anti-viral and anti-bacterial.
- Layer 2 Additional wear layer providing added durability and a second line of defense against stains.
- Layer 3 The industry's highest quality print film.
- Layer 4 Embossed, compressed backing with fiberglass reinforcement _ to resist tears and gouging and allow better adhesion.





Anti-Viral


Anti-Bacterial

Organic/inorganic materials infused into UV layer JP0612352A0001V

- Reduces the number of specific viruses on the product by 99% or more.
- SIAA marking indicates products that have been quality-controlled and disclosed such information in accordance to the guidelines of the Society of International sustaining growth for Antimicrobial Articles based on the results evaluated by ISO21702.
- Complies with SIAA safety standards.
- Antiviral processing is not intended for the treatment or prevention of illnesses.

SIAA Reg. #: JP0612352A0001V

Images and graphics not to scale




















3078

Beige Micro Tweed



Beige Stone Cloud

Bronze Antique Oak

3029

3047

















Tweed 4008 Ashen Herringbone



TOLI Coordination

Mature AdVantage is part of the TOLI Coordination System which was developed to link all TOLI product lines together through color allowing you to create the highest performing spaces with complimentary products.

The TOLI Coordination System is not a matching program. It's a program that allows you to easily find colors and designs that will work together across all TOLI product lines - Sheet, HVT and LVT.



FAS-2072

TKA-7054

TOLI Coordination

Allowing for ideal product selection while enhancing the creativity and continuity of design.







FAS-2010

TKA-7022



LTA-510

TKA-7061

Recommended Product Applications

The following application chart is provided to aid in understanding where our flooring products are recommended for use. This application chart is a subjective recommendation and is predicated upon the adherence to proper installation techniques; specific location of installation; level of foot traffic; and the type and professional level of maintenance practiced on-site. As there is a wide range of variables within an environment and the characteristics of each application may vary significantly, please consult with your CBC® Flooring sales representative to determine which CBC Flooring product is appropriate for your installation.

/ Pathways / ads

*

*

*

*

*

*

*

*

*

*

 $\star |\star$

 $\star | \star$

 $\star | \star$

 $\star |\star$

 $\star |\star$


 \star

 $\star | \star$

 $\star |\star| \star |\star|$

 $\star |\star| \star |\star|$





Residence Room

Staff Lounge

Shower Area/Room

Storage/Utility Room

Stairway/Landing (interior/




★ Recommended

Recommended Product Applications



Office	Mature AdVantage	Homogeneous Vinyl Tile	Lightwood / Kareina Asento	Piesta	Nattice / Pathways / Stair Tre ads
Break Area/Vending Area	*	*	*	*	*
Cafeteria/Dining Area	*	*	*	*	*
Corridor (exterior)					*
Corridor (interior)	*	*	*	*	*
Elevator	*	*	*	*	*
Entryway/Foyer	*	*	*	*	*
Lavatory	*	*	*	*	*
Lobby	*	*	*	*	*
Office/Admin/Conf. Room	*	*	*	*	*
Parking Garage Walkway/ Elevator (exterior					*
Ramp (interior/exterior)					*
Stairway/Landing (interior/ exterior)					*
Storage/Utility Room	*	*	*	*	*



	nstitutional	Mature AdVantage	Homogeneous Vinyl Tile	Lightwood / Kareina Asento	Piesta	Nattice / Pathways / Stair Tre ads
	Airport-Baggage Claim		*	*	*	*
	Airport-Check In/Security		*	*	*	*
	Airport-Gate Area	*	*	*	*	*
	Airport-Jet Bridge					*
	Airport-Office	*	*	*	*	*
	Airport-Retail	*	*	*	*	*
	Arena/Stadium (exterior)					*
	Arena/Stadium (interior)	*	*	*	*	*
	Cafeteria/Dining/Break Area	*	*	*	*	*
i	Church	*	*	*	*	*
	Civic/Convention Center	*	*	*	*	*
	Corridor (exterior)					*
	Corridor (interior)	*	*	*	*	*
	Courthouse	*	*	*	*	*
	Funeral Home	*	*	*	*	*
	Lavatory	*	*	*	*	*
	Library	*	*	*	*	*
	Museum	*	*	*	*	*
	Office/Admin/Conf. Room	*	*	*	*	*
	Parking Garage Walkway/ Elevator (exterior)					*
	Poolside (interior/exterior)					*
	Prison	*	*	*	*	*
	Ramp (interior/exterior)					*
	Stairway/Landing (interior/ exterior)					*
	Storage/Utility Room	*	*	*	*	*
	Water Park					*

★ Recommended

Note: Takiron products are not recommended in commercial kitchens and immediate adjacent areas.

Resistance to Staining & Chemicals per ASTM F 925

	Surface Dulling			:	Surface Attack			Color Change				
Agent	Mature® AdVantage	Kareina Asento®	Homogeneous Vinyl Tile	Nattice™/Pathways/ Stair Treads	Mature AdVantage	Kareina Asento	Homogeneous Vinyl Tile	Nattice/Pathways/ Stair Treads	Mature AdVantage	Kareina Asento	Homogeneous Vinyl Tile	Nattice/Pathways/ Stair Treads
Acetic Acid - 5%	0	0	0	0	0	0	0	0	0	0	0	0
Acetic Acid - 28%	0	0	0	0	0	0	0	0	0	0	0	0
Ammonia - 5%	0	0	0	0	0	0	0	0	0	0	0	0
Ammonium Hydroxide - 10%	0	0	0	0	0	0	0	0	0	0	0	0
Ammonium Hydroxide - 30%	0	0	0	0	0	0	0	0	0	0	0	0
Aniline Blue - 2.5%	0	0	0	0	0	0	0	0	1	0	3	2
Bleach - 5%	0	0	0	0	0	0	0	0	0	0	0	0
Dialysis Solution	0	0	0	0	0	0	0	0	0	3	0	0
Ethyl (Denatured) Alcohol	0	0	0	0	0	0	0	0	0	0	0	0
Formaldehyde - 37%	0	0	0	0	0	0	0	0	0	0	0	0
Giesma Blood Stain	0	0	0	0	0	0	0	0	3	3	3	3
Hand Sanitizer (Alcohol Based)	0	0	0	0	0	0	0	0	0	0	0	0
Hema 3 Solution	0	0	0	0	0	0	0	0	0	0	0	0
Hydrochloric Acid - 5%	0	0	0	0	0	0	0	0	0	0	0	0
Hydrochloric Acid - 38%	0	0	0	0	0	0	0	0	0	0	0	0
Hydrogen Peroxide - 30%	0	0	0	0	0	0	0	0	0	0	0	0
Kerosene	0	0	0	0	0	0	0	0	0	0	0	0
Mineral Oil	0	0	0	0	0	0	0	0	0	0	0	0
Olive Oil	0	0	0	0	0	0	0	0	0	1	0	0
Phenol - 5%	0	0	0	0	0	0	0	0	0	1	1	0
Phenolic Disinfectant Cleaner	0	0	0	0	0	0	0	0	0	1	0	2
Potassium Hydroxide - 15%	0	0	0	0	0	0	0	0	0	0	0	0
Quaternary Disinfectant Cleaner	0	0	0	0	0	0	0	0	0	1	0	0
Rubbing Alcohol (5% Isopropyl)	0	0	0	0	0	0	0	0	0	0	0	0
Sodium Hydroxide - 5%	0	0	0	0	0	0	0	0	0	0	0	0
Sodium Hydroxide - 15%	0	0	0	0	0	0	0	0	0	0	0	0
Sodium Hydroxide - 50%	0	0	0	0	0	0	0	0	0	0	0	0
Sulfuric Acid - 5%	0	0	0	0	0	0	0	0	0	0	1	0
Turpentine	0	0	0	0	0	0	0	0	0	0	0	0
Unleaded Gasoline (Regular Grade)	0	0	0	0	0	0	0	0	0	0	0	3
Uric Acid	0	0	0	0	0	0	0	0	0	1	0	0

^{0 -} No Change

Notes:

According to ASTM, the F925 test method is subjective and test results are nonnumeric;

This test is not a stain test - it is intended to determine the effect specific chemicals (or agents) will have on the surface of the flooring;

The flooring product is tested without any applied sealers or floor finishes;

For the most accurate results, CBC America recommends using the customer's chemicals on actual product samples that have been treated with the maintenance products to be used on the finished floor;

Flooring sample material for testing is readily available from CBC America;

For more detailed information, please contact CBC America.

^{1 -} Slight Change

^{2 -} Moderate Change

^{3 -} Severe Change

Product Characteristics

Standard Spec	ASTM 1303
Classification	Type I Grade 1
Backing Class	Class B
Nominal Dimensions	6' Wide x 66' Long (1828mm x 20m)
Roll Size	44 Square Yards
Overall Thickness	2.0mm (0.080")
Wear Layer Thickness	0.5mm (0.02")
Recycled Contents Pre-Consumer Post-Consumer MR Credit 4.1	>14.5% >14.0% 21.25% (Sum of Post-Consumer + 1/2 Pre-Consumer)
Warranty	Mature AdVantage is covered by a limited 15-year warranty. Visit our website, www.cbcflooring.com , for complete details.



Test Performance

	Characteristic	Test Method	Requirement	Performance
	Thickness	ASTM F386	≥ 0.040"	Passes. (0.080")
	Wear Layer Thickness - Grade 1 (Commercial)	ASTM F410	≥ 0.020"	Passes. 0.5mm (0.020") with additional reinforced urethane top coat.
က	Wear Layer Composition - Type 1	Certificate of Compliance	≥ 90% binder	Passes. With embedded anti-viral properties.
F1303	Indentation	ASTM F1914	≤ 0.012"	Passes. (0.004" as tested)
ASTM F	Flexibility	ASTM F137	1/4 mandrel, no cracks or breaks	Passes.
AS	Chemical Resistance	ASTM F925	No more than slight change in surface dulling, surface attack, or staining.	Passes.
	Resistance to Heat	ASTM F1514	ΔE ≤ 8.0	Passes. (ΔE ≤ 1.0 as tested)
	Resistance to Light	ASTM F1515	ΔE ≤ 8.0	Passes. (ΔE ≤ 1.0 as tested)
	Static Load Limit (@175psi)	ASTM F970	≤ 0.005"	Passes. (0.001" as tested)
S	Static Load Limit (Modified)	ASTM F970	≤ 0.005"	500 psi. (0.003" as tested) 750 psi. (0.005" as tested)
Additional Tests	Static Coefficient of Friction	ASTM D2047	≥ 0.5	≥ 0.6 ADA Compliant
	Critical Radiant Flux	ASTM E648	0.45 W/cm ² or more-Class I	Class I (> 0.45 W/cm ²)
	Smoke Generation	ASTM E662	450 or less	<450 (Flaming and Non-flaming)
	VOC Emissions	CA 01350	TVOC ≤ 0.5 mg/m ³	Passes. FloorScore Certified FS-03031
	Anti-Viral	ISO21702	SIAA ISO 21702 Anti Virus	Destroys >99% in 24 hours SIAA Reg. #: JP0612352A0001V

Visit our web site @ www.cbcflooring.com for installation instructions, maintenance procedures and detailed specifications.



TOLI Mature®AdVantage

Commercial Sheet with ClearGuard[™] Anti-Viral Wear Layer











CBC Flooring is committed to advance sustainability

by marketing the finest flooring products from around the globe. Our EcoVision™ Policy supports environmental responsibility for the world we all share. We strive to reduce waste, limit the consumption of natural resources and preserve Earth's environment for future generations.

For more information and sample requests, contact CBC Flooring:

919-230-8700 www.cbcflooring.com



GET SAMPLES FAST 919-230-8700 www.cbcflooring.com

Questions? Give us a call, we're ready to help you create your next great space.