

Adhesive Reference Chart



	Product	RH Limit ASTM 2170	Vapor Emission ASTM F1899	pH Limit	Weight (lbs) per Unit	Trowel Size and Usage Notes	Unit Size	Coverage per Unit	Recommended			TOLI®						C.I. TAKIRON®			
									Wet or Flood Washed	Extreme Heat or Cold	Heavy Static Load	iNStride Versa	Mature® AdVantage®	Kareina Asento®	Homogeneous Vinyl Tile	Rain Control / Dust Control	Exchome	Nattice® & Pathways (Interior)*	Nattice & Pathways (Exterior)	Tread & Risers (Interior)	Tread & Risers (Exterior)
Adhesives	TOLI® 5001 Acrylic	85%	6 lbs / 24 hours / 1,000 SF	10 pH	40.0	1/16 x 1/16 x 1/16 V-notch	4 Gallon	670-750 SF										P		P	
						1/16 x 1/16 x 1/16 V-notch	4 Gallon	720-800 SF												N	
						1/32 x 1/16 x 1/32 U-notch	4 Gallon	880-1,040 SF				P	P	P	P	P	P				
						1/32 x 1/16 x 1/32 U-notch	4 Gallon	1,200-1,400 SF				N	N	N	N	N	N	N			
	TOLI 951 Epoxy	90%	8 lbs / 24 hours / 1,000 SF		29.0	1/32 x 1/16 x 1/32 U-notch	1 Gallon	175-225 SF	•	•	•	•	•	•	•	•	•	•	•	•	•
Tread Accessories	Opti-Tape 9.5" Width				7.3		1 roll/ctn	165 LF per roll												•	
	TOLI 800 Nose Caulk				1.7	Double Caulking Gun	13.5 oz. Tube	40 LF per tube		•										•	•

P = Porous surface
 N = Non-porous surface
 • = Porous & non-porous surface
 * = Interior wet areas follow exterior instructions

TOLI-North America
 Phone: (910) 999-TOLI (8654)
 Website: www.toli-na.com
 E-Mail: info@toli-na.com
 07-25

TOLI Corporation and C.I. Takiron Corporation are ISO 9001 and ISO 14001 certified.
 TOLI-NA®, Kareina Asento® and Nattice® are trademarks of TOLI North America.
 C.I. TAKIRON® and  are trademarks of C.I. Takiron Corporation.
 TOLI® and Mature® AdVantage® are trademarks of TOLI Corporation.