

Adhesive Reference Chart



									Recommended			TOLI®								C.I. TAKIRON®			
Product	RH Limit ASTM 2170	Vapor Emission ASTM F1869 (24 hours /1,000sf)	pH Limit	Weight (lbs) per Unit	Trowel Size and Usage Notes		Unit Size	Coverage per Unit	Wet or Flood Washed	Extreme Heat or Cold	Heavy Static/Rolling Load	iNStride Versa	Mature® AdVantage®, Floorleum	Hitoe AdVantage	Kareina Asento®	Homogeneous Tile	Rain Control / Dust Control	Exchrome	Nattice® & Pathways (Interior) ¹	Nattice & Pathways (Exterior)	Tread & Risers (Interior)	Tread & Risers (Exterior)	
Adhesives	TOLI 5001 Acrylic	90%	6 lbs	10 pH	40.0	1/16 x 1/16 x 1/16 V-notch	4 Gallon	670-750 SF												P		P	
						1/16 x 1/16 x 1/16 V-notch	4 Gallon	720-800 SF														N	
						1/32 x 1/16 x 1/32 U-notch	4 Gallon	880-1,040 SF				P	P	P	P	P	P	P					
						1/32 x 1/16 x 1/32 U-notch	4 Gallon	1,200-1,400 SF				N	N	N	N	N	N	N	N				
	TOLI 295 2-part polyurethane	90%	8 lbs		12.0	1/32 x 1/16 x 1/32 U-notch	.92 Gallon	150-200 SF	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
		95% → 5 lbs																					
	TOLI 951 Epoxy	90%	8 lbs		29.0	1/32 x 1/16 x 1/32 U-notch	.92 Gallon	125-175 SF	●	●	●	●	●		●	●	●		●	●	●	●	
Tread Accessories	Opti-Tape 9.5" Width				7.3		1 roll/ctn	165 LF per roll													●		
	TOLI 800 Nose Caulk				1.7	Double Caulking Gun	13.5 oz. Tube	40 LF per tube		●											●	●	

P = Porous surface

N = Non-porous surface

• = Porous & non-porous surface

¹ = Interior wet areas follow exterior instructions

TOLI-North America
Phone: (910) 999-TOLI (8654)
Website: www.toli-na.com
E-Mail: info@toli-na.com
07-26

TOLI Corporation and C.I. Takiron Corporation are ISO 9001 and ISO 14001 certified.
TOLI-NA®, Kareina Asento® and Nattice® are trademarks of TOLI North America.
C.I. TAKIRON® and  are trademarks of C.I. Takiron Corporation.
TOLI® and Mature® AdVantage® are trademarks of TOLI Corporation.